

Easy - Pave

Grid Size	330 x 330 x 40mm Deep
Wall Thickness	4mm
Wall Depth	40mm
Weight/m ²	4.14kg/m ²
Number of grids per m ²	9
Load Capacity	Up to 250 tonnes/m ²
Axle Weight	Up to 16 tonnes
m ² per pack	1 m ²
Gross Weight of pack	5 kg
Material	100% Recycled UV Stable Polyolefin from UK sources
Temperature Stability	-50 to +90°C
Chemical Resistance	Sodium Chloride (rocksalt), ammonia, acid rain, petroleum products, hydrocarbons

Estimated Installation Time	5-10 minutes per pack (depending upon ground preparation)
Base Specifications	Minimum base recommended: 250mm for car parking 450mm for heavier vehicle
Applications and suggested usage	General purpose domestic parking filling with gravel or grass; drives, overflow parking; ground stabilisation for footpaths, banks and ditches, paddocks and farms, gateways, green roofs and golf courses etc.
Installation Information	
Filling	Easy Pave can be filled with a wide range of materials including grass seed, gravel, stones, earth and sand.
Blinding and Leveling	Level any possible unevenness in the base layer and provide a zone suitable for root growth
Base Layer	A level, firm base layer should be provided. For weed control under gravel a membrane can be used